

# Tolvi - Recirculating Designer Ceiling Hood

## CEILING-MOUNTED | FILTERING / RECIRCULATING

90 / 120 cm • 1 motor • up to 1,300 m³/h • Bluetooth remote control

### PRODUCT DETAILS

|                 |                                      |
|-----------------|--------------------------------------|
| Product type    | Ceiling cooker hood                  |
| Operating mode  | Filtering / recirculating            |
| Installation    | Ceiling-mounted                      |
| Width           | 90 / 120 cm                          |
| Motor count     | 1                                    |
| Maximum airflow | 1,300 m³/h                           |
| Colours         | Scotch-Brite stainless steel / white |
| Controls        | Bluetooth remote control             |

### ELECTRICAL & FILTRATION

|                     |                         |
|---------------------|-------------------------|
| Voltage             | 220–240 V               |
| Frequency           | 50–60 Hz                |
| Rated power         | 200 W                   |
| Maximum pressure    | 450 Pa                  |
| Maximum noise level | 63 dB                   |
| Air outlets         | 6 × 100 × 30 mm         |
| Grease filter       | Aluminium, 345 × 358 mm |
| Odour filter        | Hi-Filter, 345 × 358 mm |

### MOTOR PERFORMANCE BY SPEED

| Measurement    | Speed 1 | Speed 2 | Speed 3 | Boost |
|----------------|---------|---------|---------|-------|
| Airflow (m³/h) | 770     | 1,050   | 1,070   | 1,300 |
| Pressure (Pa)  | 139     | 264     | 347     | 450   |
| Power (W)      | 158     | 159     | 160     | 170   |
| Noise (dB)     | 60      | 64      | 65      | 67    |

### LIGHTING

|                |      |
|----------------|------|
| Light source   | LED  |
| Lighting power | 30 W |

### SHIPPING INFORMATION

|                 |                 |
|-----------------|-----------------|
| Carton size     | 95 × 66 × 65 cm |
| Shipping weight | 34 kg           |

# Energy & product data

## REGULATORY PERFORMANCE DATA

Values transcribed from the supplied product sheet; airflow and noise values follow its stated test conditions.

### ENERGY LABEL DATA

|                                   |            |
|-----------------------------------|------------|
| Annual energy consumption         | 58 kWh/a   |
| Energy efficiency class           | A          |
| Fluid dynamic efficiency          | 33.1       |
| Fluid dynamic efficiency class    | A          |
| Lighting efficiency               | 32         |
| Lighting efficiency class         | A          |
| Grease filtering efficiency       | 80         |
| Grease filtering efficiency class | C          |
| Airflow at minimum speed          | 285 m³/h   |
| Airflow at maximum normal speed   | 1,285 m³/h |
| Airflow at boost speed            | 1,415 m³/h |
| Sound power at minimum speed      | 52 dB      |
| Sound power at maximum speed      | 58 dB      |
| Sound power at boost speed        | 67 dB      |
| Power consumption in off mode     | 0.9 W      |
| Power consumption in standby mode | 0.9 W      |

### ADDITIONAL PERFORMANCE DATA

|                                              |          |
|----------------------------------------------|----------|
| Time increase factor                         | 0.8      |
| Energy efficiency index                      | 47.5     |
| Airflow at maximum efficiency point          | 450 m³/h |
| Pressure at maximum efficiency point         | 347 Pa   |
| Electrical power at maximum efficiency point | 176 W    |
| Nominal lighting system power                | 30 W     |
| Average illumination on cooking surface      | 170 lux  |
| Sound pressure level at maximum power        | 63 dB    |

Technical data is indicative and may vary when technical components change.

Test standards listed on the source sheet: EU 65/2014, EN 61591, EN 60704-2-13, EN 50564 and EU 66/2014.